

Make	Honda
Model	HT3813
Y.O.M	1985-1987
Last Update	01/01/26



## Approved Dimensions & Specifications (mm)

Eligible Racing Class	BLMRA Group 4
Drive Method	Shaft Drive (no < 0.75 of length)
Wheelbase	1145
Front Track (from outside to outside of tyres)	950
Rear Track (from outside to outside of tyres)	950
Front Tyre size	13 x 5 x 6 (minimum)
Rear Tyre size	15 x 6 x 6 (minimum)
Engine Size	As per current BLMRA regs
Engine Manufacturer	As per current BLMRA regs
Engine Alignment (centre of crankshaft to front of chassis)	n/a
Height of Front of chassis (ground to top)	254
Height of Rear of chassis (ground to top)	254
Height of Dash board from top of chassis	445
The front of chassis to leading edge of dashboard measured at deck level	n/a
Length of bonnet	n/a
Width of Bonnet at widest point	535
Depth of bonnet at deepest point	254
Chassis width at edge to edge of foot plates	760
Overall chassis length	1510
Front of chassis to centre of rear axle	1384
Seat Height (centre of axle to underside of seat base panel)	190 (minimum)

## Construction Notes & Permitted Modifications

The chassis is of a pressed steel nature with a bonnet over. Most notably the engine is low in the chassis, and offset from the centre line of the mower. The engine is a Horizontal unit with a shaft drive system of drive mechanism  
 In order to achieve the appropriate height from underside of seat to centre line of rear axle the minimum amount of metal-work may be removed to accommodate this. Note should be made that excessive removal of material in this area will require replacement at the discretion of the race committee / scrutineer. Metal may be removed to achieve the optimum seat height however this must be done after raising the rear axle within the chassis. The shaft drive must remain the Primary drive and must remain in the original transmission tunnel position.