

Make	Murray
Model	120/76
Y.O.M	2002-2004
Last Update	01/01/26



Approved Dimensions & Specifications (mm)

Eligible Racing Class	BLMRA Group 4
Drive Method	Belt Drive
Wheelbase	1219
Front Track (from outside to outside of tyres)	914
Rear Track (from outside to outside of tyres)	914
Front Tyre size	13 x 5 x 6 (minimum)
Rear Tyre size	15 x 6 x 6 (minimum)
Engine Size	As per current BLMRA regs
Engine Manufacturer	As per current BLMRA regs
Engine Alignment (centre of crankshaft to front of chassis)	130
Height of Front of chassis (ground to top)	254
Height of Rear of chassis (ground to top)	254
Height of Dash board from top of chassis	394
The front of chassis to leading edge of dashboard measured at deck level	318
Length of bonnet	686
Width of Bonnet at widest point	495
Depth of bonnet at deepest point	229
Chassis width at edge to edge of foot plates	730
Overall chassis length	1308
Front of chassis to centre of rear axle	1178
Seat Height (centre of axle to underside of seat base panel)	190 (minimum)

Construction Notes & Permitted Modifications

Built of pressed steel construction, rear body, mud guards foot boards and centre spine pressed in one piece. Main chassis consists of pressed steel channel section. Dash assy made up of pressed steel in two pieces. Fuel tank (1.4 gal) mounted as standard inside top of dash assy. Bonnet made up of two steel pressings, with air vents in top face.

In order to achieve the appropriate height from underside of seat to centre line of rear axle the minimum amount of metal-work may be removed to accommodate this. Note should be made that excessive removal of material in this area will require replacement at the discretion of the race committee / scrutineer.