

Make	John Deere
Model	110
Y.O.M	1963-1974
Last Update	01/01/26



Approved Dimensions & Specifications (mm)

Eligible Racing Class	BLMRA Group 4
Drive Method	Belt Drive
Wheelbase	1118
Front Track (from outside to outside of tyres)	889
Rear Track (from outside to outside of tyres)	889
Front Tyre size	13 x 5 x 6 (minimum)
Rear Tyre size	15 x 6 x 6 (minimum)
Engine Size	As per current BLMRA regs
Engine Manufacturer	As per current BLMRA regs
Engine Alignment (centre of crankshaft to front of chassis)	203
Height of Front of chassis (ground to top)	254
Height of Rear of chassis (ground to top)	254
Height of Dash board from top of chassis	432
The front of chassis to leading edge of dashboard measured at deck level	533
Length of bonnet	787
Width of Bonnet at widest point	356
Depth of bonnet at deepest point	165
Chassis width at edge to edge of foot plates	622
Overall chassis length	1295
Front of chassis to centre of rear axle	1130
Seat Height (centre of axle to underside of seat base panel)	190 (minimum)

Construction Notes & Permitted Modifications

This is an all-steel chassis and bodywork construction with the exception of the Bonnet which is fiberglass.

In order to achieve the appropriate height from underside of seat to centre line of rear axle the minimum amount of metal-work may be removed to accommodate this. Note should be made that excessive removal of material in this area will require replacement at the discretion of the race committee / scrutineer.