

Make	Honda
Model	HT3810
Y.O.M	1985-1989
Last Update	01/01/26



Approved Dimensions & Specifications (mm)

Eligible Racing Class	BLMRA Group 4
Drive Method	Shaft Drive > 0.75 of length
Wheelbase	1149
Front Track (from outside to outside of tyres)	890
Rear Track (from outside to outside of tyres)	890
Front Tyre size	13 x 5 x 6 (minimum)
Rear Tyre size	15 x 6 x 6 (minimum)
Engine Size	As per current BLMRA regs
Engine Manufacturer	As per current BLMRA regs
Engine Alignment (centre of crankshaft to front of chassis)	454/133 offset from cntr of mower
Height of Front of chassis (ground to top)	254
Height of Rear of chassis (ground to top)	254
Height of Dash board from top of chassis	438
The front of chassis to leading edge of dashboard measured at deck level	457
Length of bonnet	768
Width of Bonnet at widest point	495
Depth of bonnet at deepest point	254
Chassis width at edge to edge of foot plates	762
Overall chassis length	1537
Front of chassis to centre of rear axle	1384
Seat Height (centre of axle to underside of seat base panel)	190 (minimum)

Construction Notes & Permitted Modifications

In order to achieve the appropriate height from underside of seat to centre line of rear axle the minimum amount of metal-work may be removed to accommodate this. Note should be made that excessive removal of material in this area will require replacement at the discretion of the race committee / scrutineer. You are not allowed to use the fuel tank under the seat. The engine can be mounted no lower than the underside of the chassis side rails. You may sink the seat into the rear panel by a maximum of 76mm to achieve the 191mm to the centre of the axle. You may not flare the wheel arches. If you have prepared it to this information the tyre should clear the wheel arch. The pole brackets and towing eye must be removed.