

Make	Husky Bolens
Model	LT8
Y.O.M	1979 - 1981
Last Update	01/01/26



Approved Dimensions & Specifications (mm)

Eligible Racing Class	BLMRA Group 4
Drive Method	Belt Drive
Wheelbase	1105
Front Track (from outside to outside of tyres)	813
Rear Track (from outside to outside of tyres)	813
Front Tyre size	13 x 5 x 6 (minimum)
Rear Tyre size	15 x 6 x 6 (minimum)
Engine Size	As per current BLMRA regs
Engine Manufacturer	As per current BLMRA regs
Engine Alignment (centre of crankshaft to front of chassis)	394
Height of Front of chassis (ground to top)	254
Height of Rear of chassis (ground to top)	254
Height of Dash board from top of chassis	356
The front of chassis to leading edge of dashboard measured at deck level	546
Length of bonnet	610
Width of Bonnet at widest point	394
Depth of bonnet at deepest point	140
Chassis width at edge to edge of foot plates	724
Overall chassis length	1346
Front of chassis to centre of rear axle	1156
Seat Height (centre of axle to underside of seat base panel)	190 (minimum)

Construction Notes & Permitted Modifications

In order to achieve the appropriate height from underside of seat to centre line of rear axle the minimum amount of metal-work may be removed to accommodate this. Note should be made that excessive removal of material in this area will require replacement at the discretion of the race committee / scrutineer.

Towing bracket on the rear to be removed. Engine mounting surface is "dished" (pressed 19mm into chassis section, so chassis top will be 254mm from ground with engine mount 248mm from ground.