

| | |
|-------------|---------------|
| Make | MTD Lawnflite |
| Model | 12/30 5 speed |
| Y.O.M | 1987– 1998 |
| Last Update | 01/01/26 |



Approved Dimensions & Specifications (mm)

| | |
|--|---------------------------|
| Eligible Racing Class | BLMRA Group 4 |
| Drive Method | Belt Drive |
| Wheelbase | 1120 |
| Front Track (from outside to outside of tyres) | 870 |
| Rear Track (from outside to outside of tyres) | 870 |
| Front Tyre size | 13 x 5 x 6 (minimum) |
| Rear Tyre size | 15 x 6 x 6 (minimum) |
| Engine Size | As per current BLMRA regs |
| Engine Manufacturer | As per current BLMRA regs |
| Engine Alignment (centre of crankshaft to front of chassis) | 240 |
| Height of Front of chassis (ground to top) | 254 |
| Height of Rear of chassis (ground to top) | 254 |
| Height of Dash board from top of chassis | 490 |
| The front of chassis to leading edge of dashboard measured at deck level | n/a |
| Length of bonnet | 660 |
| Width of Bonnet at widest point | n/a |
| Depth of bonnet at deepest point | n/a |
| Chassis width at edge to edge of foot plates | n/a |
| Overall chassis length | n/a |
| Front of chassis to centre of rear axle | n/a |
| Seat Height (centre of axle to underside of seat base panel) | 190 (minimum) |

Construction Notes & Permitted Modifications

In order to achieve the appropriate height from underside of seat to centre line of rear axle the minimum amount of metal-work may be removed to accommodate this. Note should be made that excessive removal of material in this area will require replacement at the discretion of the race committee / scrutineer.